



SIZE	ART. NO.	EAN NO.
5	6614-5	7340118316079
6	6614-6	7340118315928
7	6614-7	7340118315942
8	6614-8	7340118315966
9	6614-9	7340118315980
10	6614-10	7340118315867
11	6614-11	7340118315881
12	6614-12	7340118315904

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 6614

Leather glove, full grain cowhide, polyester, Cat. II, black, grey, withstands contact heat up to 100°C, water and oil repellent palm, elasticated 180°, for fine assembly work

### PROPERTIES

High level of protection, good fingertip sensitivity, extra flexible, durable, excellent grip in oily environments, perfect fit, comfortable, breathable

### SPECIFICATION

TYPE OF GLOVE All-round work gloves, Assembly gloves

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain cowhide

BACK MATERIAL Polyester

DEXTERITY 5

FASTENING Elasticated 180°

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex, polyester

## TEGERA® 6614

### FEATURES

Withstands contact heat up to 100°C, specially designed thumb, water and oil repellent palm, soft

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with oil

### PRIMARY ENVIRONMENTS OF USE

Slippery environments, oily and greasy environments, harsh environments

### PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, construction, engineering, installation work, machine driving, soil preparation, transport work, warehouse work

### PRIMARY INDUSTRIES OF USE

Oil, gas, petrochemical, pulp and paper, machinery and equipment, MRO, automotive, transportation, building and construction

### TYPE OF WORK

Light weight

CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
3011X



EN 407:2004  
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 6614

### EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

### EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
3011X



EN 407:2004  
X1XXXX

