



TEGERA® 464OR

Textile glove, 15 gg, Merino Wool, nylon, spandex, Cat. II, black, inner Glove, for touchscreen, elasticated 360°, for allround work

PROPERTIES

Comfortable, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves, Textile gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINING MATERIAL 15 gg, Merino Wool, Nylon, Spandex

DEXTERITY 5

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

FASTENING Elasticated 360°

LENGTH RANGE 195-250 mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Hangtag with euro slot

OUTER MATERIAL SPECIFICATION Nylon, Merino wool, elastane

SIZE	ART. NO.	EAN NO.
6	4640R-6	7340118365930
7	4640R-7	7340118366029
8	4640R-8	7340118366111
9	4640R-9	7340118366203
10	4640R-10	7340118366296
11	4640R-11	7340118366388

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 464OR

FEATURES

For touchscreen, soft

PREVENTS RISK OF

Contact with cold

PRIMARY ENVIRONMENTS OF USE

Cold environments

PRIMARY AREAS OF USE

Airport work, building and construction, fishing industry work, petro-chemical work, transport work

PRIMARY INDUSTRIES OF USE

Oil, gas, petrochemical, transportation, building and construction

TYPE OF WORK

Medium weight

2(3)

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
214XX



EN 511:2006
X1X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-23

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 4640R

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold

Suitable for contact with foodstuffs



CE Cat. II

EN 420:2003 + A1:2009

EN 388:2016 214XX

EN 511:2006 X1X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.