



TEGERA® 513

Leather glove, full grain goatskin, cotton, Cat. II, black, green, white, reinforced index finger, reinforced fingers and thumb, hook-and-loop, for assembly work

PROPERTIES

Good fingertip sensitivity, flexible, durable, good grip, good fit

SPECIFICATION

TYPE OF GLOVE All-round work gloves, Assembly gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin

BACK MATERIAL Cotton

DEXTERITY 5

FASTENING Hook-and-loop

COLOUR Black, Green, White

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Hook with hangtag

SIZE	ART. NO.	EAN NO.
6	513-6	7340118363141
7	513-7	7340118363233
8	513-8	7340118363325
9	513-9	7340118363417
10	513-10	7340118363509
11	513-11	7340118363592
12	513-12	7340118363684

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 513

FEATURES

Reinforced index finger, reinforced fingers and thumb, specially designed thumb

PREVENTS RISK OF

Prevents risk of: abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments, dirty environments

PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, construction, engineering, installation work, machine driving, machine operating, transport work, warehouse work

PRIMARY INDUSTRIES OF USE

Pulp and paper, automotive, transportation, utilities, building and construction

TYPE OF WORK

Medium weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



TEGERA® 513

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com