

TEGERA® 70

Cut sleeve, cut resistance level B, 13 gg, basalt fibre thread, CRF® Technology, nylon, polyester, spandex, Cat. II, black, bulk pack, elasticated 360°, for allround work

PROPERTIES

High level of protection, flexible, durable, perfect fit, comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant sleeves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 11.7

SIZE RANGE (EU) 8, 9, 10

LINING MATERIAL 13 gg, Basalt fibre thread, CRF® Technology, Nylon, Polyester, Spandex

FASTENING Elasticated 360°

LENGTH RANGE 420-490 mm

COLOUR Black

PIECES PER PACKAGE/CARTON 6/60

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION HPPE, basalt fibre thread, nylon, elastane, polyester



SIZE	ART. NO.	EAN NO.
8	70-8	7340118341248
9	70-9	7340118341231
10	70-10	7340118341255

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 70

FEATURES

Approved for handling foodstuffs

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments

PRIMARY AREAS OF USE

Assembly, building and construction, engineering, inspection work, installation work, machine operating, metalwork, warehouse work

PRIMARY INDUSTRIES OF USE

Metal fabrication, machinery and equipment, MRO, automotive, transportation, building and construction, logistics

TYPE OF WORK

Medium weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X4XB



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 70

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

Suitable for contact with foodstuffs



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X4XB



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com