



CRF[®]

SIZE	ART. NO.	EAN NO.
6	441-6	7340118356709
7	441-7	7340118356792
8	441-8	7340118356884
9	441-9	7340118356976
10	441-10	7340118357065
11	441-11	7340118357157

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA[®] 441

Cut resistant glove, nitrile, nitrile foam, 3/4 dipped, double-dipped, sandy finish, cut resistance level B, 13 gg, CRF[®] Technology, nylon, spandex, Cat. II, black, grey, withstands contact heat up to 100°C, DMF (DMFa) free, oil and grease resistant palm, for allround work

PROPERTIES

Durable, good grip in oily environments

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

PRODUCTGLOVECUTRESISTANCEENISO13997 Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 5.9

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

DIPPING 3/4 dipped, double-dipped

DIPPING MATERIAL Nitrile, nitrile foam

LINING MATERIAL 13 gg, CRF[®] Technology, Nylon, Spandex

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE, nylon, elastane

TEGERA® 441

FEATURES

Withstands contact heat up to 100°C

PREVENTS RISK OF

Cut injuries, scratches, lacerations, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, oily and greasy environments, harsh environments

PRIMARY AREAS OF USE

Building and construction, machine operating, metalwork

PRIMARY INDUSTRIES OF USE

Agriculture, mining, metal fabrication, machinery and equipment, MRO, building and construction

TYPE OF WORK

Medium weight

2(3)

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X43B



EN 407:2004
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 441

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X43B



EN 407:2004
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com