



TEGERA® 88800

Leather glove, full grain cowhide, Cat. II, white, withstands contact heat up to 250°C, extra long, reinforced index finger, reinforced seams, hook-and-loop, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip, good fit

SPECIFICATION

TYPE OF GLOVE All-round work gloves, Assembly gloves, Heat protection gloves, Heavy duty gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain cowhide

BACK MATERIAL Full grain cowhide

DEXTERITY 5

CUFF STYLE Extended safety cuff

CUFF MATERIAL Leather

FASTENING Hook-and-loop

COLOUR White

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
6	88800-6	7340118316789
7	88800-7	7340118315331
8	88800-8	7340118315355
9	88800-9	7340118315379
10	88800-10	7340118315294
11	88800-11	7340118315317
12	88800-12	7340118316819

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 88800

FEATURES

Withstands contact heat up to 250°C, extra long, reinforced index finger, reinforced palm, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

PRIMARY AREAS OF USE

Engineering, hot work, metalwork, mining, welding

PRIMARY INDUSTRIES OF USE

Mining, oil, gas, petrochemical, metal fabrication

TYPE OF WORK

Heavy weight

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3143X



EN 407:2004
42314X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 88800

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II

EN 420:2003 + A1:2009



EN 388:2016 3143X



EN 407:2004 42314X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com