



 1228W

EN ISO 20349-2:2017 S3, SRC, CI, HRO, HI, WG EN ISO 20345:2011 S3, SRC, CI, HRO, HI, WG ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

MID-CUT BOOT WITH HIDDEN BOA® FIT SYSTEM

Our most comfortable and durable welding boot with the best possible protection. The BOA® Fit system enables perfect fit and for extra protection it is covered by PU-coated leather. Specially treated leather with KEVLAR® thread in the seams provides heat resistance with a max operating limit of 427°C and a long-term heat exposure limit of 204°C. The oil and heat-resistant nitrile outer sole means excellent grip and JALAS® composite toe cap, steel nail penetration insert and double impact protection zones in PORON® XRD® help prevent injuries.

CHARACTERISTICS	FUNCTIONS
• Good grip • Extra comfortable • Excellent shock absorption	• ProNose toe reinforcement • Water repellent • Anti-static properties • KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit) • Heat-resistant upper • Heat-resistant outsole • Oil-resistant outsole • Padded boot shaft • Ventilating insole • BOA® Fit System



PREVENTS RISK OF

toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Regular

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyamide

INSOLE FX2 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Grey, Yellow

NET WEIGHT, (SIZE 42) 1,42 kg

COMPLIANCE




EN ISO 20345:2011
S3, SRC, CI, HRO, HI, WG



ASTM F2413-18
M/I/C
SD 35 PR

EN ISO 20349-2:2017
S3, SRC, CI, HRO, HI, WG



FEATURES



Anti-static properties



Heat-resistant upper



Oil-resistant outsole



ProNose toe reinforcement



Composite toecap



Ergothan Shock Absorption System



Nail protection in steel



Heat-resistant outsole



Water repellent

SIZE	ARTICLE NUMBER	EAN
35	1228W-35	6408487523571
36	1228W-36	6408487523618
37	1228W-37	6408487523656
38	1228W-38	6408487523694
39	1228W-39	6408487523731
40	1228W-40	6408487523779
41	1228W-41	6408487523816
42	1228W-42	6408487523854
43	1228W-43	6408487523892
44	1228W-44	6408487523939
45	1228W-45	6408487523977
46	1228W-46	6408487524011
47	1228W-47	6408487524059
48	1228W-48	6408487524097

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com